

# SpeakWalls™ Dry-Erase Solutions Inc.

1.888.224.5988 | Speakwalls.com

## SpeakWalls™ Magnetic Dry Erase Wallcovering: MAG50G

This proprietary material is featured an advanced high-tech composite construction, it combines a magnet-receptive layer backer with premium fabric for a wide range of surfaces, including walls, columns, and more. Pairing with MAG59G, this extension panel stretches writable, magnet-receptive surface all the way from floor to ceiling – creating one unified, high-performance collaboration wall.

### Product Specifications

| Product Name                    | Product Code | Surface finish | Roll Size          | Width             | Total Weight<br>oz./sq. feet           |
|---------------------------------|--------------|----------------|--------------------|-------------------|--|
| Magnetic Dry Erase Wallcovering | MAG50G       | Gloss          | 50'<br>15.24 meter | 50"<br>1.27 meter | 5.80 oz./sq. feet<br>1.77 kg/sq. meter |

| Total Weight               | Magnet-receptive | Total Thickness | Flame Resistance       | Abrasion Resistance                             |  |
|----------------------------|------------------|-----------------|------------------------|---|--|
| 72.46 oz./LY<br>2.25 kg/LM | Yes              | 28mil<br>0.7mm  | Class A<br>(ASTM E-84) | 25,000 Double rubs<br>(ASTM D3597)<br>Wyzenbeek |  |

### Benefits

- Magnet-Receptive Surface: compatible with magnetic pins for seamless and effortless presentation setups.
- Superior erasability: cleans off effortlessly without leaving marks.
- Resistant to abrasion, stains, and solvents: maintains a pristine appearance even under heavy use.
- Exceptional durability: long-lasting performance for extended use.
- No yellowing or ghosting: stays clear and bright over time.
- Easy cleaning: no harsh cleaners required for maintenance.
- 10-year limited warranty: backed by a decade of quality assurance.

### Shipping Details

- Continuous, seamless 50 LF rolls: ensures a smooth, uninterrupted application.
- Secure packaging: wound on a sturdy 3.5" x 59" core for safe transit.
- Approximate package weight 88.13lbs: manageable for handling and installation.
- Shipping method: delivered via UPS/FedEx Ground for reliable service.

All products are sold on the condition that the purchaser is responsible for evaluating their suitability for intended use. No warranty, express or implied, including warranty of merchantability or fitness for a particular purpose, is provided. This does not constitute sellers products specifications.  
SpeakWalls is registered trademark.